



---

|                 |                      |                    |               |
|-----------------|----------------------|--------------------|---------------|
| Power           | <b>7,5 W</b>         | Voltage            | <b>230 V</b>  |
| Luminous flux** | <b>730 lm (360°)</b> | Colour temperature | <b>6000 K</b> |
| Light colour    | <b>CW</b>            | Beam angle         | <b>110 °</b>  |
| Base            | <b>GU10</b>          | Protection class   | <b>IP20</b>   |

---



 Declaration of Conformity

Technical data:

|                           |               |
|---------------------------|---------------|
| Product code              | WOJ+14594     |
| Power                     | 7,5 W         |
| Nominal current           | 40 mA         |
| Voltage                   | 230 V         |
| Energy efficiency classe  | F             |
| Energy consumption        | 8 kWh/1000h   |
| Frequency                 | 50HZ Hz       |
| Useful luminous flux*     | 600 lm (120°) |
| Luminous flux**           | 730 lm (360°) |
| Light efficiency          | 97 lm/W       |
| Luminous intensity        | 270 cd        |
| Colour temperature        | 6000 K        |
| Light colour              | CW            |
| Beam angle                | 110 °         |
| RA                        | >80           |
| Dimmable                  | No            |
| Working temperature range | -20 to +40 °  |
| Lifespan                  | 17000 h       |
| Base                      | GU10          |
| Protection class          | IP20          |
| Dimension (axbxc)         | 50X56 mm      |
| Weight                    | 0.022 kg      |
| For use                   | Inside        |
| Made in                   | PRC           |

