




CE

Power	<b>10 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>975 lm (120°)</b>	Colour temperature	<b>4000 K</b>
Light colour	<b>Neutral white</b>	Beam angle	<b>100 °</b>
IK	<b>07</b>	Protection class	<b>IP65</b>



See more on dedicated page 



 Declaration of Conformity



 Photometric file

**Technical data:**

Product code	SLI029052NW_PW
Power	10 W
Nominal current	45 mA
Voltage	230 V
Energy consumption	10 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	975 lm (120°)
Luminous flux**	975 lm (360°)
Light efficiency	98 lm/W
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	100 °
RA	>70
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, GLASS
IK	07
Protection class	IP65
Colour	White
Dimension (axbxc)	90x75x27 mm
Weight	0.159 kg
For use	Outside
Assembly method	On the ceiling
Application	EXT
Made in	PRC



\*Applies to the LED source used. \*\*Luminaire luminous flux