



Power	<b>25 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>3000 lm (120°)</b>	Colour temperature	<b>4000 K</b>
Light colour	<b>Neutral white</b>	Beam angle	<b>120 °</b>
IK	<b>07</b>	Protection class	<b>IP65</b>



 Declaration of Conformity



 Photometric file

**Technical data:**

Product code	SLI028034NW
Power	25 W
Nominal current	120 mA
Voltage	230 V
Energy efficiency classe	E
Energy consumption	25 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.9
Useful luminous flux*	3000 lm (120°)
Luminous flux**	3000 lm (360°)
Light efficiency	120 lm/W
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	120 °
RA	80
Light source included	+
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	plastic
IK	07
Protection class	IP65
Dimension (axbxc)	600x60x52 mm
Weight	0.68 kg
For use	Outside
Assembly method	On the ceiling/Suspended
Made in	PRC



\*Applies to the LED source used. \*\*Luminaire luminous flux