



**CE**

Power **5,3 W**

Voltage **12 V**

Colour temperature **6000 K**

Light colour **CW**

Beam angle **120 °**

Protection class **IP20**

**Technical data:**

|                              |                   |
|------------------------------|-------------------|
| Product code                 | SLI040035CW       |
| Power                        | 5,3 W             |
| Nominal current              | 442 mA            |
| Voltage                      | 12 V              |
| Energy consumption           | 6 kWh/1000h       |
| Frequency                    | DC Hz             |
| Protection class             | III               |
| Power factor                 | 1                 |
| Luminous flux**              | 400 lm (360°)     |
| Light efficiency             | 75 lm/W           |
| Colour temperature           | 6000 K            |
| Light colour                 | CW                |
| Beam angle                   | 120 °             |
| RA                           | 80                |
| Uniformity of color SDCM max | 5                 |
| Dimmable                     | Yes               |
| Working temperature range    | -20/+40 °         |
| Lifespan                     | 17000 h           |
| Housing material             | Aluminum, PLASTIC |
| Protection class             | IP20              |
| Colour                       | SREBRNY           |
| Dimension (axbxc)            | 500x29x10 mm      |
| Weight                       | 0.108 kg          |
| For use                      | Inside            |
| Assembly method              | On the ceiling    |
| Application                  | INT               |
| Made in                      | PRC               |



\*Applies to the LED source used. \*\*Luminaire luminous flux