



CE

---

Power	<b>36 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>4500 lm (360°)</b>	Colour temperature	<b>4000 K</b>
Light colour	<b>Neutral white</b>	Beam angle	<b>120 °</b>
Protection class	<b>IP65</b>		

---



 User manual



 Declaration of Conformity

Technical data:

Product code	SLI028030NW_PW
Power	36 W
Nominal current	155 mA
Voltage	230 V
Energy consumption	36 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power factor	0.9
Useful luminous flux*	4500 lm (360°)
Luminous flux**	4200 lm (360°)
Light efficiency	125 lm/W
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	120 °
RA	80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	plastic
Protection class	IP65
Colour	White
Dimension (axbxc)	1237x53x27 mm
Weight	0.45 kg
For use	Inside/Outside
Assembly method	On the ceiling/Suspended
Application	Inside/Outside
Made in	PRC



\*Applies to the LED source used. \*\*Luminaire luminous flux