




| | | | |
|----------------|-----------------------|--------------------|---------------|
| Power | 100 W | Voltage | 230 V |
| Luminous flux* | 8300 lm (120°) | Colour temperature | 4000 K |
| Light colour | Neutral white | Beam angle | 85 ° |
| IK | 08 | Protection class | IP65 |



See more on dedicated page 



 User manual



 Declaration of Conformity



 Photometric file

Technical data:

| | |
|------------------------------|------------------|
| Product code | SLI029056NW_PW |
| Power | 100 W |
| Nominal current | 430 mA |
| Voltage | 230 V |
| Energy consumption | 100 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | I |
| Power factor | 0.99 |
| Useful luminous flux* | 8300 lm (120°) |
| Luminous flux** | 8300 lm (360°) |
| Light efficiency | 83 lm/W |
| Luminous intensity | 5100 cd |
| Colour temperature | 4000 K |
| Light colour | Neutral white |
| Beam angle | 85 ° |
| RA | >80 |
| Light source included | + |
| Uniformity of color SDCM max | 5 |
| Dimmable | No |
| Working temperature range | -20 to +40 ° |
| Lifespan | 50000 h |
| Housing material | Aluminum+PC LENS |
| IK | 08 |
| Protection class | IP65 |
| Colour | Gray |
| Dimension (axbxc) | 294x215x30 mm |
| Weight | 0.95 kg |
| For use | Outside |
| Assembly method | On the ceiling |
| Application | EXT |
| Made in | PRC |



*Applies to the LED source used. **Luminaire luminous flux