



Power	45 W	Voltage	230 V
Luminous flux*	5950 lm (360°)	Colour temperature	6000 K
Light colour	CW	Beam angle	120 °
IK	06	Protection class	IP20



 User manual



 Declaration of Conformity

Technical data:

Product code	SLI035037CW_PW
Power	45 W
Nominal current	200 mA
Voltage	230 V
Energy consumption	45 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.95
Useful luminous flux*	5950 lm (360°)
Luminous flux**	4600 lm (360°)
Light efficiency	132 lm/W
Colour temperature	6000 K
Light colour	CW
Beam angle	120 °
RA	>80
Uniformity of color SDCM max	3
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum, PLASTIC
IK	06
Protection class	IP20
Colour	White
Dimension (axbxc)	595x595x10 mm
Mounting hole	575x575 mm
Weight	2.09 kg
For use	Inside
Assembly method	Recessed/On the ceiling/Suspended
Application	INT
Made in	PRC
Other	L80B50 50000h MTBF 80000h ,



*Applies to the LED source used. **Luminaire luminous flux