

**CE**


---

Power	<b>38 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>6600 lm (360°)</b>	Colour temperature	<b>4000 K</b>
Light colour	<b>Neutral white</b>	Beam angle	<b>120 °</b>
IK	<b>10</b>	Protection class	<b>IP65</b>

---

**Technical data:**

Product code	SLI028025NW_PW_BLACK
Power	38 W
Nominal current	180 mA
Voltage	230 V
Energy consumption	38 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.98
Useful luminous flux*	6600 lm (360°)
Luminous flux**	5900 lm (360°)
Light efficiency	174 lm/W
Luminous intensity	2000 cd
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	120 °
RA	80
Uniformity of color SDCM max	3
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	POLYCARBONATE
IK	10
Protection class	IP65
Colour	Black/White
Dimension (axbxc)	1250x72x70 mm
For use	Inside/Outside
Assembly method	On the ceiling/Suspended
Application	INT/EXT
Made in	PRC
Other	MAX 22 pcs per line ,



\*Applies to the LED source used. \*\*Luminaire luminous flux