




CE

Power	<b>30 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>4400 lm (360°)</b>	Colour temperature	<b>4000 K</b>
Light colour	<b>Neutral white</b>	Beam angle	<b>120 °</b>
IK	<b>06</b>	Protection class	<b>IP20</b>



See more on dedicated page 



 User manual



 Declaration of Conformity



 Photometric file

Technical data:

Product code	SLI035049NW
Power	30 W
Nominal current	135 mA
Voltage	230 V
Energy consumption	30 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.9
Useful luminous flux*	4400 lm (360°)
Luminous flux**	3800 lm (360°)
Light efficiency	146 lm/W
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	120 °
RA	80
Uniformity of color SDCM max	3
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum, PLASTIC
IK	06
Protection class	IP20
Colour	White
Dimension (axbxc)	595x595x12 mm
Mounting hole	575x575 mm
Weight	2.8 kg
For use	Inside
Assembly method	Recessed/On the ceiling/Suspended
Application	INT
Made in	PRC



\*Applies to the LED source used. \*\*Luminaire luminous flux