



Power **35 W**

Voltage **230 V**

Colour temperature **4000 K**

Light colour **Neutral white**

Beam angle **60 °**

Protection class **IP20**



 Declaration of Conformity



 Photometric file



 3D model

CEL42PRO3584060W

Technical data:

| | |
|------------------------------|----------------|
| Product code | WOJP02482 |
| Power | 35 W |
| Nominal current | 167.4 mA |
| Voltage | 230 V |
| Energy consumption | 35 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | II |
| Power supply included | + |
| Manufacturer of power supply | TRIDONIC |
| Power factor | 0.93 |
| Useful luminous flux* | 4725 lm (360°) |
| Luminous flux** | 3850 lm (360°) |
| Light efficiency | 135 lm/W |
| Colour temperature | 4000 K |
| Light colour | Neutral white |
| Beam angle | 60 ° |
| RA | 80 |
| Light source included | + |
| Producer of LED diodes | CREE |
| Uniformity of color SDCM max | 3 |
| Dimmable | OPC |
| Working temperature range | -20/+40 ° |
| Lifespan | 50000 h |
| Housing material | Aluminum |
| Protection class | IP20 |
| Colour | White |
| Dimension (axbxc) | 180x130 mm |
| Mounting hole | Ø145 mm |
| Weight | 1.11 kg |
| For use | Inside |
| Assembly method | Recessed |
| Application | Inside |
| Made in | PL |



*Applies to the LED source used. **Luminaire luminous flux