



CE

Power **27 W**

Voltage **230 V**

Colour temperature **4000 K**

Light colour **Neutral white**

Beam angle **40 °**

Protection class **IP20**



 Declaration of Conformity



 Photometric file

MDR46PRO2784040W

**Technical data:**

Product code	WOJP03362
Power	27 W
Nominal current	129.1 mA
Voltage	230 V
Energy consumption	27 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Manufacturer of power supply	TCI
Power factor	0.93
Useful luminous flux*	3780 lm (360°)
Luminous flux**	2970 lm (360°)
Light efficiency	140 lm/W
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	40 °
RA	80
Light source included	+
Producer of LED diodes	CREE
Uniformity of color SDCM max	3
Dimmable	OPC
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum
Protection class	IP20
Colour	White
Dimension (axbxc)	99 x 125 x 167 mm
Weight	1.11 kg
For use	Inside
Assembly method	On 3-circuit system
Application	Inside
Made in	PL



\*Applies to the LED source used. \*\*Luminaire luminous flux