



CE

Power	<b>75 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>13000 lm (360°)</b>	Colour temperature	<b>4000 K</b>
Light colour	<b>Neutral white</b>	Beam angle	<b>120 °</b>
IK	<b>10</b>	Protection class	<b>IP65</b>



See more on dedicated page 



 User manual



 Declaration of Conformity



 Photometric file

**Technical data:**

Product code	SLI028027NW_PW
Power	75 W
Nominal current	332 mA
Voltage	230 V
Energy consumption	75 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.99
Useful luminous flux*	13000 lm (360°)
Luminous flux**	11200 lm (360°)
Light efficiency	173 lm/W
Luminous intensity	3600 cd
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	120 °
RA	80
Uniformity of color SDCM max	3
Dimmable	No
Working temperature range	-25/+40 °
Lifespan	50000 h
Housing material	POLYCARBONATE
IK	10
Protection class	IP65
Colour	Gray/White
Dimension (axbxc)	1550x72x70 mm
Weight	1.3917 kg
For use	Inside/Outside
Assembly method	On the ceiling/Suspended
Application	INT/EXT
Made in	PRC
Other	MAX 10 pcs per line ,



\*Applies to the LED source used. \*\*Luminaire luminous flux