



CE

Power **100 W**
Luminous flux* **14600 lm (360°)**
Light colour **Neutral white**
IK **9**

Voltage **230 V**
Colour temperature **4000 K**
Beam angle **130/80 °**
Protection class **IP66**




See more on dedicated page 



 Declaration of Conformity



 Photometric file

Technical data:

Product code	SLI027015NW_PW
Power	100 W
Nominal current	430 mA
Voltage	230 V
Energy consumption	100 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power factor	0.9
Useful luminous flux*	14600 lm (360°)
Luminous flux**	14000 lm (360°)
Light efficiency	146 lm/W
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	130/80 °
RA	70
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum, PLASTIC
IK	9
Protection class	IP66
Colour	Gray
Dimension (axbxc)	536x166x77 mm
Mounting hole	60 mm
Weight	1.75 kg
For use	Outside
Assembly method	On a pole
Application	EXT
Made in	PRC
Other	100-265V ,



*Applies to the LED source used. **Luminaire luminous flux