



| | | | |
|-----------------|----------------------|--------------------|---------------|
| Power | 5,5 W | Voltage | 230 V |
| Luminous flux** | 475 lm (360°) | Colour temperature | 3000 K |
| Light colour | WW | Beam angle | 38 ° |
| Base | GU10 | | |



 Declaration of Conformity

Technical data:

| | |
|------------------------------|---------------------------------------|
| Product code | WOJ+14696 |
| Power | 5,5 W |
| Nominal current | 30 mA |
| Voltage | 230 V |
| Energy efficiency classe | F |
| Energy consumption | 6 kWh/1000h |
| Frequency | 50HZ Hz |
| Power factor | 0.5 |
| Useful luminous flux* | 400 lm (90°) |
| Luminous flux** | 475 lm (360°) |
| Light efficiency | 73 lm/W |
| Luminous intensity | 600 cd |
| Colour temperature | 3000 K |
| Light colour | WW |
| Beam angle | 38 ° |
| RA | 80 |
| Uniformity of color SDCM max | 5 |
| Dimmable | Yes |
| Working temperature range | -20/+40 ° |
| Lifespan | 17000 h |
| Base | GU10 |
| Dimension (axbxc) | 50x53 mm |
| Weight | 0.023 kg |
| Made in | PRC |
| Other | WOJ+06586; BERKER 2973, 296110;286710 |

