

## PHE 15 16.7 4T TA (766 616)

- For use in wet weather conditions
- For overhead contact lines of electrical railways
- With self-testing element
- Visual indication
- Easy transport due to detachable insulating sticks
- Consisting of four elements
- Storage bag included in delivery



Figure without obligation

Figure without obligation

Kit includes:			
Pos. No.	Part No.	Pos. No.	Part No.
1	766 619	7	766 076
2	766 678	8	766 077
3	766 677	9	766 889
4	766 072	10	766 602
5	766 075	11	766 704
6	766 073		

For more detailed information on these products, see Accessory chapter

Type	PHE 15 16.7 4T TA
Part No.	766 616
Nominal voltage (U <sub>N</sub> )	15 kV
Type of voltage	a.c.
Frequency	16.7 Hz
Total length (l <sub>Σ</sub> )	4890 mm
Insulating clearance (l <sub>i</sub> )	685 mm
Insertion depth (l <sub>o</sub> )	1675 mm
Length of the prod	1900 mm
Length of the operating stick (with hand guard)	640 mm
Length of the operating stick (end fitting)	2530 mm
DB drawing No.	3 Ebgw 02.51
DB material No.	237 129
Standard	DIN VDE 0681-6
Design	Complete
For use at	☀
For	Outdoor installations
Application	Overhead contact lines of electric railways
Version	Single-pole
Indication	Visual
Self-testing element	Yes
Battery	Lithium
Material (test electrode)	St/gal Zn
Material (test prod)	Glass-fibre reinforced polyester tube
Material (indicator)	Plastic, fully insulated
Material (insulating stick)	Glass-fibre reinforced polyester tube
Weight	5,09 kg
Customs tariff number (Comb. Nomenclature EU)	90303370
GTIN	4013364126091
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.