

UK 25 SQL (773 236)

- Earthing and short-circuiting devices can be configured online by means of the earthing and short-circuiting configurator



Figure without obligation




Figure without obligation

*) Clamping range and maximum cable cross-section of universal clamps used for:

| Fixed ball point Ø | Phase T pin collar width | Rd / FI clamping range | Cable cross-section |
|--------------------|--------------------------|------------------------|---------------------|
| 20/25/30 mm | 15/18 mm | 20/30 mm | 16 mm ² |
| 20/25/30 mm | 15/18 mm | 20/30 mm | 25 mm ² |
| 20/25/30 mm | 15/18 mm | 20/30 mm | 35 mm ² |
| 20/25/30 mm | 15/18 mm | 20/30 mm | 50 mm ² |
| 20/25/30 mm | 15/18 mm | 20/30 mm | 70 mm ² |
| 20/25/30 mm | 15/18 mm | - | 95 mm ² |
| -/25/30 mm | - | - | 120 mm ² |
| - | - | - | 150 mm ² |

| Type | UK 25 SQL |
|---|---|
| Part No. | 773 236 |
| For fixed ball point Ø | 20 / 25 mm |
| For T pins with a collar width of | 15 mm |
| Rd / FI clamping range | 20 mm |
| Anti-rotation protection | PK1 |
| For cable cross-section Cu | 16 ... 120 ¹⁾ mm ² |
| Max. short-circuit current I _k 0.5 s | 33.5 kA |
| Max. short-circuit current I _k 1 s | 23.7 kA |
| Standard | EN/IEC 61230 (DIN VDE 0683-100), threaded T pin shaft DIN 48087 |
| Temperature range | -25 °C ... +55 °C |
| Material (pressure plate) | St/gal Zn |
| Material (clamp body) | Copper alloy/gal Sn |
| Material (shaft) | Copper alloy/gal Sn |
| Weight | 714 g |
| Customs tariff number (Comb. Nomenclature EU) | 85359000 |
| GTIN | 4013364114579 |
| PU | 1 pc(s) |

¹⁾ See table for „Clamping range and maximum cable cross-section of universal clamps used for“

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.

The clamps must be designed for the same maximum short-circuit current as the earthing and short-circuiting cables!