


APC 60 62 (785 758)



Figure without obligation

Figure without obligation

Find the right size to get the perfect fit with your DEHNcare personal protective equipment.



DEHNcare ArcClassic jacket and trousers										DEHNcare ArcClassic coat									
Standard men's sizes (cm)																			
Ordering size	40	42	44	46	48	50	52	54	56	58	60	62	64	66	68	70	72	74	76
Body size	165-177	168-180	171-183	174-186	176-188	178-190	180-192	182-194	184-196	186-198	188-200	190-202	192-204	194-206	196-208	198-210	200-212	202-214	204-216
Chest measurement	92-95	96-100	101-103	104-107	106-111	112-115	116-119	119-123	124-127	128-132	133-137	138-142	143-147	148-152	153-157	158-162	163-167	168-172	173-177
Waistband	79-82	82-86	87-90	91-94	95-98	99-102	103-107	108-111	112-115	116-119	120-123	124-127	128-132	133-137	138-142	143-147	148-152	153-157	158-162
Hip size	104	106	110	114	118	122	126	130	134	138	142	146	150	154	158	162	166	170	174
Inside leg length	83.5	84.5	85.5	86	86.5	87	87.5	-	-	-	-	-	-	-	-	-	-	-	-
Sleeve length	69.6	70.2	70.6	71.4	72	72.6	73.2	71	73	75	77	79	-	-	-	-	-	-	-

- Reinforced stand-up collar
- Zip and hook-and-loop fasteners

Type	APC 60 62
Part No.	785 758
Arc fault protection class (box test 7 kA / 0.5 s – single-pole)	APC 2
Arc energy (W_{arc} or W_{LEP})	320 kJ
Extended electric arc energy (W_{arc} or W_{LEP}) (based on box test)	630 kJ
EuroTest PIP001 (10 kA / 1 s – three-pole)	Yes
Arc Rating – ATPV (Open Arc Test)	33.1 cal / cm ²
PPE category (NFPA 70E)	PPE 3
Size (international)	60 / 62 (XXL)
Outer material	Siliconised calf grain leather, 100% Kevlar interlock knit
Inner material	100% cotton
Material (sewing thread)	100% Kevlar
Standard	IEC 61482-2, EN ISO 14116
Weight	3,21 kg
Customs tariff number (Comb. Nomenclature EU)	42031000
GTIN	4013364245150
PU	1 pc(s)

In case of very heavy soiling, the protective coat can be dry cleaned by a specialist leather cleaner.

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.