


SR D50 4700 FS22 2500 IP HVI GFK V2A (105 317)



Figure without obligation



Supporting tube with internal sealing end and EB spring element. Air-termination rod $\varnothing 22/16/10$ mm.

Type	SR D50 4700 FS22 2500 IP HVI GFK V2A
Part No.	105 317
Material of air-termination rod	StSt
Length of air-termination rod	2500 mm
Material of supporting tube	GRP / StSt
Length of supporting tube	4700 mm
Transport length	4700 mm
Outside diameter \varnothing	50 mm
Length of insulating clearance	1535 mm
Wall thickness	3 mm
Material factor km	0.7
Permanent temperature range	-50 °C ... +100 °C
Type	UV-stabilised
Sleeve	60 x 5 mm
Max. free length with air-termination rod (wall mounting)	5500 mm
Max. gust wind speed	(Max. free length 5,500 mm, 1x HVI inside) 185 km/h
Max. gust wind speed	(Max. free length 5,500 mm, 1x HVI outside) 149 km/h
Max. gust wind speed	(Max. free length 5,500 mm, 4x HVI outside) 137 km/h
Pull-out force with a length of 500#mm	200 N (supporting tube insulator as per 62561-8)
Bending force with a length of 500#mm	200 N (supporting tube insulator as per 62561-8)
Standard	DIN IEC/TS 62561-8 (VDE V 0185-561-8)
Weight	17,12 kg
Customs tariff number (Comb. Nomenclature EU)	85389099
GTIN	4013364157811
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.