


## SR D50 5000 FS22 10 2500 IP HVIP GFK V2A (105 323)



Figure without obligation



Supporting tube with internal sealing end and EB spring element. Air-termination rod  $\varnothing 22 / 16 / 10$  mm.

| Type  | SR D50 5000 FS22 10 2500 IP HVIP GFK V2A                  |
|---|---|
| Part No.  | 105 323   |
| Material of air-termination rod                           | StSt  |
| Length of air-termination rod                             | 2500 mm   |
| Material of supporting tube                               | GRP / StSt  |
| Length of supporting tube                                 | 5000 mm   |
| Outside diameter $\varnothing$                            | 50 mm   |
| Transport length  | 5000 mm   |
| Wall thickness  | 4 mm  |
| Material factor km  | 0.7   |
| Length of insulating clearance                            | 1800 mm   |
| Permanent temperature range                               | -50 °C ... +100 °C  |
| Type  | UV-stabilised   |
| Sleeve  | 60 x 5 mm   |
| Suitable for installation outside the tube                | no  |
| Max. free length with air-termination rod (wall mounting) | 5500 mm   |
| Max. gust wind speed                                      | (Max. free length 5,500 mm, 1x HVI power inside) 159 km/h |
| Pull-out force with a length of 500#mm                    | 200 N (supporting tube insulator as per 62561-8)          |
| Bending force with a length of 500#mm                     | 200 N (supporting tube insulator as per 62561-8)          |
| Standard  | DIN IEC/TS 62561-8 (VDE V 0185-561-8)                     |
| Weight  | 16,3 kg   |
| Customs tariff number (Comb. Nomenclature EU)             | 85389099  |
| GTIN  | 4013364152403   |
| PU  | 1 pc(s)   |

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.