


## SR D50 5000 FS2500 IP SA HVIP GFK V2A (105 395)



Figure without obligation



Supporting tube with internal sealing end and EB spring element. Air-termination rod  $\varnothing 22 / 16 / 10$  mm.

| Type  | SR D50 5000 FS2500 IP SA HVIP GFK V2A            |
|---|--|
| Part No.                                      | 105 395  |
| Material of air-termination rod               | StSt   |
| Length of air-termination rod                 | 2500 mm  |
| Material of supporting tube                   | GRP / StSt                                       |
| Length of supporting tube                     | 5000 mm  |
| Outside diameter $\varnothing$                | 50 mm  |
| Transport length                              | 5000 mm  |
| Wall thickness                                | 4 mm   |
| Material factor km                            | 0,7  |
| Length of insulating clearance                | 1800 mm  |
| Permanent temperature range                   | -50 °C ... +100 °C                               |
| Type  | UV stabilised                                    |
| Sleeve  | 60 x 5 mm  |
| Suitable for installation outside the tube    | no   |
| Pull-out force with a length of 500#mm        | 200 N (supporting tube insulator as per 62561-8) |
| Bending force with a length of 500#mm         | 200 N (supporting tube insulator as per 62561-8) |
| Standard                                      | DIN IEC/TS 62561-8 (VDE V 0185-561-8)            |
| Weight  | 17,12 kg   |
| Customs tariff number (Comb. Nomenclature EU) | 85389099   |
| GTIN  | 4013364157934                                    |
| PU  | 1 pc(s)  |

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.