



## BA 30X3.5 STTZN R25M (852 335)




Figure without obligation

Steel strip according to EN 62561-2 with zinc coating  $\geq 70 \mu\text{m}$  on average (about  $500 \text{ g/m}^2$ ), for lightning protection and earth-termination systems.

Type Part No.	BA 30X3.5 STTZN R25M 852 335 ✓
Width	30 mm
Thickness	3.5 mm
Cross-section	$105 \text{ mm}^2$
Material	St/tZn
Standard	EN 62561-2
Zinc coating	$\geq 70 \mu\text{m}$ average (about $500 \text{ g/m}^2$ )
Conductivity	$\geq 6.66 \text{ m} / \text{Ohm mm}^2$
Resistivity	$\leq 0.15 \text{ Ohm mm}^2 / \text{m}$
Short-circuit current (AC 50 Hz / DC) (1 s; $\leq 300 \text{ }^\circ\text{C}$ )	7.4 kA
Length tolerance	+/- 5%
Weight	840 g/m
Customs tariff number (Comb. Nomenclature EU)	72123000
GTIN	4013364031067
PU	25 m

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.

Strips in different dimensions and materials are available upon request.