

SR D30 2640 FSP10 1000 GFK AL V2A (105 280)



Figure without obligation

Supporting tube with internal sealing end and air-termination rod \varnothing 10 mm.

Type	SR D30 2640 FSP10 1000 GFK AL V2A
Part No.	105 280
Material of supporting tube	GRP / Al
Length of supporting tube	2640 mm
Length of air-termination tip	1000 mm
Material of air-termination tip	StSt
Transport length	2640 mm
Outside diameter \varnothing GRP	30 mm
Outside diameter \varnothing Al (clamping range)	40 mm
Length of insulating clearance	1070 mm
Wall thickness	3 mm
Material factor km	0.7
Permanent temperature range	-50 °C ... +100 °C
Type	UV stabilised
Sleeve	40 x 5 mm
Max. gust wind speed	(Max. free length 3,040 mm, 1x HVI light inside) 201 km/h
Max. free length	3040 mm
Min. clamping length	600 mm
Standard	DIN IEC/TS 62561-8 (VDE V 0185-561-8)
Weight	3,59 kg
Customs tariff number (Comb. Nomenclature EU)	85389099
GTIN	4013364255838
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.