


DG ME YPV SCI 1500 (952 520)


- Prewired modular complete unit for use in photovoltaic systems consisting of a base part and plug-in protection modules
- Combined disconnection and short-circuiting device with safe electrical isolation in the protection module (patented SCI principle)
- Tried and tested fault-resistant Y circuit



Figure without obligation



Basic circuit diagram DG ME YPV SCI 1500



Dimension drawing DG ME YPV SCI 1500

Modular multipole surge arrester with three-step d.c. switching device for PV systems.

| Type | DG ME YPV SCI 1500 |
|---|---|
| Part No. | 952 520 |
| SPD according to EN 61643-11 / IEC 61643-11 | type 2 / class II |
| Max. PV voltage (U_{CPV}) | 1500 V |
| Short-circuit current rating (I_{SCPV}) | 10 kA |
| Total discharge current (8/20 μ s) (I_{total}) | 25 kA |
| Nominal discharge current (8/20 μ s) [(DC+/DC-) --> PE] (I_n) | 12.5 kA |
| Voltage protection level (U_P) | ≤ 6 kV |
| Response time (t_A) | ≤ 25 ns |
| Operating temperature range (T_U) | -40 °C ... +80 °C |
| Operating state / fault indication | green / red |
| Number of ports | 1 |
| Cross-sectional area (min.) | 1.5 mm ² solid / flexible |
| Cross-sectional area (max.) | 35 mm ² stranded / 25 mm ² flexible |
| For mounting on | 35 mm DIN rails acc. to EN 60715 |
| Enclosure material | thermoplastic, red, UL 94 V-0 |
| Place of installation | indoor installation |
| Degree of protection | IP 20 |
| Capacity | 4.5 module(s), DIN 43880 |
| Approvals | KEMA, UL |
| Weight | 501 g |
| Customs tariff number (Comb. Nomenclature EU) | 85354000 |
| GTIN | 4013364149069 |
| PU | 1 pc(s) |

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.