



RD 10 STTZN L3000 (800 910)



Figure without obligation

With zinc coating $\geq 50 \mu\text{m}$ on average (about 350 g/m^2). Suitable for installation in reinforcements (e.g. concrete supports or concrete foundations).

Type	RD 10 STTZN L3000
Part No.	800 910 ✓
Diameter \varnothing conductor	10 mm
Cross-section	78 mm^2
Material	St/tZn
Standard	based on EN 62561-2
Zinc sheath	$\geq 50 \mu\text{m}$ average (about 350 g/m^2)
Conductivity	$\geq 6.66 \text{ m} / \text{Ohm mm}^2$
Resistivity	$\leq 0.25 \text{ Ohm mm}^2 / \text{m}$
Short-circuit current (AC 50 Hz / DC) (1 s; $\leq 300 \text{ }^\circ\text{C}$)	5.5 kA
Length	3 m
Length tolerance	+/- 5%
Weight	1,85 kg
Customs tariff number (Comb. Nomenclature EU)	72149939
GTIN	4013364253315
PU	10 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.

Conductor materials can only be supplied in the original coil weights.
Further conductor materials as specified in the standard series EN 62561-2 are available on request.