


PCE data sheet

article#	045-9
article description	CEE-plug 125A 5p 9h IP67 POWER TWIST
description long	CEE-plug 125A 5p 9h IP67 POWER TWIST housing material: PA6 rated current: 125A number of poles: 5 (3P+N+PE) clock-position: 9h rated voltage/frequency: 120/208V~ - 144/250V~ / 50+60Hz contacts: brass nickel plated, with pilot pin connection technology: frame terminals with screws IP protection class: IP66/IP67
GTIN (EAN)	9003399041136
country of origin	AT
customs number	85366990
net weight	1.169 kg
packaging quantity	2
minimum order quantity	2



ETIM 8.0	EC000140
IEC-amperage	125 A
Number of poles	5
Voltage according to EN 60309-2	200 - 250 V (50+60 Hz) blue
Clock hour position	9 h
Identification colour	Blue
RAL-number	7046
Degree of protection (IP)	IP67
Connection system	Screwed terminal
Cable entry	Gland nut
Angle of plug	Straight
Material	Plastic
Contact material	CuZn
Surface treatment contacts	Nickel-plated



a	270 mm
b	131 mm
K (cable Ø)	22,5-50 mm
SW	81 mm
wire flexible	16-50 mm ²
contact screws	450 Ncm
strain relief	1500 Ncm
dismantling length	100 mm
stripping length	24-27 mm



<https://www.pcelectric.at/shop/en/?func=detail&artnr=045-9>



www.manufacturer-safety.info