


PCE data sheet

article#	444-7
article description	CEE-flanged socket sloping (120x130) 125A 4p 7h IP67 POWER TWIST
description long	CEE-flanged socket sloping (120x130) 125A 4p 7h IP67 POWER TWIST housing material: PA6 rated current: 125A number of poles: 4 (3P+PE) clock-position: 7h rated voltage/frequency: 480-500V~ / 50+60Hz contacts: brass, with lamellar spring (CuBe) connection technology: frame terminals with screws dimensions (flange/fixing center): 120x130 mm / 100x108 mm IP protection class: IP66/IP67
GTIN (EAN)	9003399061554
country of origin	AT
customs number	85366990
net weight	0.896 kg
packaging quantity	2

ETIM 7.0	EC001317
IEC-amperage	125 A
Voltage acc. EN 60309-2	500 V (50+60 Hz) black
Number of poles	4
Clock hour position	7 h
Identification colour	Black
Degree of protection (IP)	IP67
Connection system	Screwed terminal
Angle of plug	Angled
Material	Plastic
Contact material	CuZn
Surface finish contacts	Untreated
Flange size vertical	130 mm
Drill hole distance vertical	108 mm
Flange size horizontal	120 mm
Drill hole distance horizontal	100 mm

wire flexible	16-50 mm ²
wire solid	16-70 mm ²
contact screws	450 Ncm
dismantling length	100 mm
stripping length	24-27 mm



www.manufacturer-safety.info