


## PCE data sheet

|                        |   |
|------------------------|---|
| article#               | <b>293-12v</b>  |
| article description    | <b>CEE-connector 32A 3p 42VAC 50/60Hz IP44 TWIST</b>  |
| description long       | CEE-connector 32A 3p 42VAC 50/60Hz IP44 TWIST<br>housing material: PA6<br>rated current: 32A<br>number of poles: 3 (3P)<br>clock-position: 12h<br>rated voltage/frequency: 42V~ / 50+60Hz<br>contacts: brass nickel plated<br>connection technology: screw terminals<br>IP protection class: IP44 |
| GTIN (EAN)             | 9003399061257   |
| country of origin      | AT  |
| customs number         | 85366990  |
| net weight             | 0.177 kg  |
| packaging quantity     | 10  |
| minimum order quantity | 10  |

|                           |                          |
|---------------------------|--------------------------|
| ETIM 7.0                  | EC001320                 |
| IEC-amperage              | 32 A                     |
| Number of poles           | 3                        |
| Voltage acc. EN 60309-2   | 40-50 V (50+60 Hz) white |
| Clock hour position       | 12 h                     |
| Degree of protection (IP) | IP44                     |
| Connection system         | Schraubklemme            |
| Angle of plug             | Straight                 |
| Cable entry               | Verschraubung            |
| Material                  | Plastic                  |

|                    |                      |
|--------------------|----------------------|
| a                  | 150 mm               |
| b                  | 75 mm                |
| K (cable Ø)        | 9,5-24 mm            |
| SW                 | 48 mm                |
| wire flexible      | 1-10 mm <sup>2</sup> |
| contact screws     | 160 Ncm              |
| strain relief      | 600 Ncm              |
| dismantling length | 70 mm                |
| stripping length   | 14-16 mm             |



[www.manufacturer-safety.info](http://www.manufacturer-safety.info)