




CE

Power	<b>10 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>850 lm (120°)</b>	Colour temperature	<b>6000 K</b>
Light colour	<b>CW</b>	Beam angle	<b>100 °</b>
Protection class	<b>IP65</b>		



See more on dedicated page 



 Declaration of Conformity



 Photometric file

Technical data:

Product code	SLI029037CW
Power	10 W
Nominal current	50 mA
Voltage	230 V
Energy consumption	10 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.5
Useful luminous flux*	850 lm (120°)
Luminous flux**	830/850 lm (360°)
Light efficiency	83 lm/W
Colour temperature	6000 K
Light colour	CW
Beam angle	100 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, GLASS
Protection class	IP65
Colour	Black
Dimension (axbxc)	83x104x23 mm
For use	Inside/Outside
Assembly method	On the ceiling
Application	INT/EXT
Made in	PRC



\*Applies to the LED source used. \*\*Luminaire luminous flux