

IP65



CE

| | | | |
|------------------|-----------------------|--------------------|---------------|
| Power | 50 W | Voltage | 230 V |
| Luminous flux* | 4000 lm (120°) | Colour temperature | 4000 K |
| Light colour | Neutral white | Beam angle | 100 ° |
| Protection class | IP65 | | |



 Declaration of Conformity



 Photometric file

Technical data:

| | |
|------------------------------|---------------------|
| Product code | SLI029044NW |
| Power | 50 W |
| Nominal current | 230 mA |
| Voltage | 230 V |
| Energy consumption | 50 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | I |
| Power supply included | + |
| Power factor | 0.9 |
| Useful luminous flux* | 4000 lm (120°) |
| Luminous flux** | 3850/4000 lm (360°) |
| Light efficiency | 77 lm/W |
| Colour temperature | 4000 K |
| Light colour | Neutral white |
| Beam angle | 100 ° |
| RA | 80 |
| Uniformity of color SDCM max | 5 |
| Dimmable | No |
| Working temperature range | -20/+40 ° |
| Lifespan | 17000 h |
| Housing material | Aluminum, GLASS |
| Protection class | IP65 |
| Colour | White |
| Dimension (axbxc) | 160x205x31 mm |
| For use | Inside/Outside |
| Assembly method | On the ceiling |
| Application | INT/EXT |
| Made in | PRC |



*Applies to the LED source used. **Luminaire luminous flux