

STREETOS 2

SLI027017NW_PW

Street luminaire STREETOS 2, with a power of 100 W, high light efficacy 140 lm/W. It is made of high-quality components, supported by a 5-year warranty. It has a very high degree of protection IP65, providing protection against the ingress of dust and water jets. IK9 class provides impact resistance. It shines with light of neutral - the most universal colour (4000K).



Power	100 W	Voltage	230 V
Luminous flux*	14000 lm (360°)	Colour temperature	4000 K
Colour of light	Neutral white	Beam angle	145/75 °
IK	9	Degree of protection (IP)	IP65

Technical data


Code	SLI027017NW_PW
Power	100 W
Nominal current	430 mA
Voltage	230 V
Energy consumption	100 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power factor	0.9
Useful luminous flux*	14000 lm (360°)
Luminous flux**	13500 lm (360°)
Lamp efficacy	140 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	145/75 °
RA	70
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum, PC
IK	9
Degree of protection (IP)	IP65
Colour	Gray
Dimension (AxBxC)	555x172x114 mm
Mounting hole	60 mm
For use	Outside
Assembly method	On a pole
Application	EXT
Made in	PRC
Other	100-277V ,

Related documents



 User manual



 Declaration of Conformity

